

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2  
Revision date: 11/07/2019

Page 1 of 12  
Print date: 11/07/2019

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: PINTURA ACRÍLICA AEROSOL 400 ml  
Product Code: ACRIXXX

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Pintura acrílica brillo.

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **Químicas Vila Hervás S.L**  
Address: Calle Perelló nº 3 (Polígono Industrial Masía del Juez)  
City: Torrent  
Province: Valencia  
Telephone: + 34 960649838  
E-mail: fulldip@fulldip.com  
Web: www.fulldip.com

**1.4 Emergency telephone number:** (Only available during office hours; Monday-Friday; 08:00-18:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

- Aerosol 1 : Pressurised container: May burst if heated.
- STOT SE 3 : May cause respiratory irritation.
- STOT SE 3 : May cause drowsiness or dizziness.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

H statements:

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H336 May cause drowsiness or dizziness.

P statements:

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.
- P271 Use only outdoors or in a well-ventilated area.
- P501 Dispose of contents/container according to law.
- P370+P378 In case of fire: Use an ABC powder fire extinguisher to extinguish.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2  
Revision date: 11/07/2019

Page 2 of 12  
Print date: 11/07/2019

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.

EUH statements:  
EUH066 Repeated exposure may cause skin dryness or cracking.

Contains:  
n-butyl acetate

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 607-025-00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01-2119485493-29-XXXX	[1] n-butyl acetate	20 - 50 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 603-019-00-8 CAS No: 115-10-6 EC No: 204-065-8 Registration No: 01-2119472128-37-XXXX	[1] dimethyl ether	25 - 50 %	Flam. Gas 1, H220	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

## SECTION 4: FIRST AID MEASURES.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2  
Revision date: 11/07/2019

Page 3 of 12  
Print date: 11/07/2019

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### **4.2 Most important symptoms and effects, both acute and delayed.**

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

## SECTION 5: FIREFIGHTING MEASURES.

The product is Extremely inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

### **5.1 Extinguishing media.**

#### **Suitable extinguishing media:**

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### **5.2 Special hazards arising from the mixture.**

#### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.
- Explosions.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### **6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### **6.2 Environmental precautions.**

Prevent the contamination of drains, surface or subterranean waters, and the ground.

### **6.3 Methods and material for containment and cleaning up.**

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### **6.4 Reference to other sections.**

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2  
Revision date: 11/07/2019

Page 4 of 12  
Print date: 11/07/2019

For exposure control and individual protection measures, see section 8.  
For later elimination of waste, follow the recommendations under section 13.

### SECTION 7: HANDLING AND STORAGE.

#### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Pressurised gases must be handled by suitably trained and experienced individuals. Use equipment suitable for supply pressure and temperature. Protect containers against physical damage and keep valves clean and in perfect condition. Do not tamper with original packaging.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. It must not be stored under conditions conducive to corrosion of the container. Protect containers against physical damage and inspect them regularly to ensure they are in good condition.

The product is not affected by Directive 2012/18/EU (SEVESO III).

#### 7.3 Specific end use(s).

Not available.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

#### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
n-butyl acetate	123-86-4	United Kingdom [1]	Eight hours	150	724
			Short term	200	966
		United States [2] (Cal/OSHA)	Eight hours	150	
			Short term	200	
		United States [3] (NIOSH)	Eight hours	150	
			Short term	200	
United States [4] (OSHA)	Eight hours	150	710		
	Short term				
dimethyl ether	115-10-6	European Union [5]	Eight hours	1000	1920
			Short term		
		United Kingdom [1]	Eight hours	400	766
			Short term	500	958

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] According Compendium of Policy Documents and Statements adopted by National Institute for Occupational Safety and Health (NIOSH).

[4] According Occupational Health and Safety Standards and US Code of Federal Regulations adopted by US Occupational Safety and Health Administration (OSHA).

[5] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2

Revision date: 11/07/2019

Page 5 of 12

Print date: 11/07/2019

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	859,7 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Local effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	859,7 (mg/m <sup>3</sup> )
	DNEL (General population)	Oral, Long-term, Systemic effects	3,4 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	3,4 (mg/kg bw/day)
dimethyl ether CAS No: 115-10-6 EC No: 204-065-8	DNEL (Workers)	Inhalation, Long-term, Systemic effects	1894 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
	STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg sediment dw)
	sediment (marine water)	0,0981 (mg/kg sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>
<b>Uses:</b>	<b>Pintura acrílica brillo.</b>
<b>Breathing protection:</b>	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.



-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2

Revision date: 11/07/2019

Page 6 of 12

Print date: 11/07/2019

Filter Type needed: A2

### Hand protection:

PPE: Work gloves.  
Characteristics: «CE» marking, category I.  
CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420  
Maintenance: Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.  
Observations: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.

Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
-----------	--------------------------	---------------------------	-------	--------------------------	------

### Eye protection:

PPE: Face shield.  
Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid.  
CEN standards: EN 165, EN 166, EN 167, EN 168  
Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.  
Observations: Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.



### Skin protection:

PPE: Anti-static protective clothing.  
Characteristics: «CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.  
CEN standards: EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5  
Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.  
Observations: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.



PPE: Anti-static safety footwear.  
Characteristics: «CE» marking, category II.  
CEN standards: EN ISO 13287, EN ISO 20344, EN ISO 20346  
Maintenance: The footwear should be checked regularly  
Observations: The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: N.A./N.A.

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: -6 °C

Flash point: -34 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: 2927

Vapour density: N.A./N.A.

Relative density: 0,76

Solubility: N.A./N.A.

Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2

Revision date: 11/07/2019

Page 7 of 12

Print date: 11/07/2019

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: En combinación con el aire se puede formar atmósfera explosiva.

Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

Extremely flammable aerosol.

Pressurised container: May burst if heated.

At high temperatures can occur pyrolysis and dehydrogenation.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.
- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
n-butyl acetate	Oral	LD50	Rat	10800 mg/kg bw [1]

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2

Revision date: 11/07/2019

Page 8 of 12

Print date: 11/07/2019

CAS No: 123-86-4      EC No: 204-658-1		[1] Acute Toxicity Data. Journal of the American College of Toxicology, Part B. Vol. 1, Pg. 196, 1992
	Dermal	LD50      Rabbit      >17600 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 7, 1974
	Inhalation	LC50      Rat      1.85 mg/l/4 h [1] [1] Inhalation Toxicology. Vol. 9, Pg. 623, 1997

a) acute toxicity;  
Not conclusive data for classification.

b) skin corrosion/irritation;  
Not conclusive data for classification.

c) serious eye damage/irritation;  
Not conclusive data for classification.

d) respiratory or skin sensitisation;  
Not conclusive data for classification.

e) germ cell mutagenicity;  
Not conclusive data for classification.

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Not conclusive data for classification.

h) STOT-single exposure;  
Product classified:  
Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;  
Not conclusive data for classification.

j) aspiration hazard;  
Not conclusive data for classification.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
n-butyl acetate	Fish	LC50	Fish	81 mg/l (96 h) [1] [1] Wellens, H. 1982. Comparison of the Sensitivity of Brachydanio rerio and Leuciscus idus by Testing the Fish Toxicity of Chemicals and Wastewaters. Z.Wasser-Abwasser-Forsch. 51(2):49-52 (GER) (ENG ABS). Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)
	Aquatic invertebrates	EC50	Daphnia sp.	44 mg/l (48 h) [1] [1] publication, 1959

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2  
Revision date: 11/07/2019

Page 9 of 12  
Print date: 11/07/2019

CAS No: 123-86-4	EC No: 204-658-1	Aquatic plants	Desmodesmus subspicatus (reported as 674.7 mg/l (72 h) [1]) Scenedesmus subspicatus
			[1] Method: other: algae growth inhibition test, according to Umweltbundesamt (German Federal Environment Agency) (proposal/draft, version February 1984)

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
n-butyl acetate CAS No: 123-86-4      EC No: 204-658-1	1,78	-	-	Very low
dimethyl ether CAS No: 115-10-6      EC No: 204-065-8	0,1	-	-	Very low

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

**Version: 2**  
**Revision date: 11/07/2019**

**Page 10 of 12**  
**Print date: 11/07/2019**

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN1950

### 14.2 UN proper shipping name.

Description:

ADR: UN 1950, AEROSOLS, 2.1, (D)

IMDG: UN 1950, AEROSOLS, 2.1 (-34°C)

ICAO/IATA (Passenger aircraft): PROHIBITED

ICAO/IATA (Cargo aircraft): UN 1950, AEROSOLS, 2.1

### 14.3 Transport hazard class(es).

Class(es): 2

### 14.4 Packing group.

Packing group: Not applicable.

### 14.5 Environmental hazards.


Marine pollutant: No

### 14.6 Special precautions for user.

ADR LQ: 1 L

IMDG LQ: 1 L

ICAO LQ: Not applicable.



Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-D,S-U

Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

#### Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): E - Special finishes (All types)

Phase I\* (from 01/01/2007): 840 g/l

Phase II\* (from 01/01/2010): 840 g/l

(\* ) g/l ready to use

VOC content (p/p): 88 %

VOC content: 672 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400 ml

**Full Dip**<sup>®</sup>  
liquid vinyl

Version: 2

Revision date: 11/07/2019

Page 11 of 12

Print date: 11/07/2019

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

Classification codes:

Aerosol 1 : Flammable aerosol, Category 1  
Flam. Gas 1 : Flammable gas, Category 1  
Flam. Liq. 3 : Flammable liquid, Category 3  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Changes in the information of the supplier (SECTION 1.3).
- Change in the hazard classification (SECTION 2.1).
- Modification in the firefighting measures (SECTION 5.2).
- Modification of ecological information values (SECTION 12.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
IATA:	International Air Transport Association.
ICAO:	International Civil Aviation Organization.
IMDG:	International Maritime Code for Dangerous Goods.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.
Log Pow:	Logarithm of the partition octanol-water.
NOEC:	No observed effect concentration.
PNEC:	Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID:	Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration,

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## ACRIXXX-PINTURA ACRÍLICA AEROSOL 400

### ml

**Version: 2**

**Revision date: 11/07/2019**

**Full Dip**<sup>®</sup>  
liquid vinyl

**Page 12 of 12**

**Print date: 11/07/2019**

Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.